

CATALOG NUMBER  
**21**

SUB. DES.  
PSURF-NO-532-NO-PGY

FOR REPLACEMENT PARTS OR  
INFORMATION ON OUR COMPLETE SITE  
AMENITIES LINE CALL:  
**1-800-452-0639**  
WWW.JAMESTOWNADVANCED.COM

**JAMESTOWN**  
ADVANCED PRODUCTS

ENCLOSURE SERIES  
TYPE 3R **3**

**Power Outlet**

**RATING 125 AMPS MAX.**

120 / 240 VOLTS AC 1 PHASE, 3 WIRE  
Total sum of breaker handles not to exceed 125 amps.  
When equipped, Meter rating : 125 amps continuous.

**SUITABLE FOR USE AS RECREATIONAL  
VEHICLE SITE SUPPLY EQUIPMENT.  
( USA and CANADA )**  
Do not bond neutral.

**NOT FOR USE AS MOBILE HOME SERVICE EQUIPMENT.**

Line terminals A, B, and N, suitable for 75° C conductors. Size conductors in accordance to load. Use copper or aluminum wire. Surface mounts 210 - #14 AWG. Pedestal units 350 MCM - #6 AWG Torque terminals to 3/16 lbs-in. See markings on breakers for their wiring and torque requirements.

Short-circuit current rating is 10,000 rms symmetrical amperes. If metered; Weather meter is not included in the short-circuit current rating. Any circuit breakers installed or replaced must be Square D with minimum ratings as noted above.

Neutral and ground bar wire size and torques.

Wire size  
14-10 AWG CU/AL 35 Lbf-in  
8 AWG CU/AL 40 Lbf-in  
6-4 AWG CU/AL 45 Lbf-in

Ground bar wire size.

Copper - #14 to #4 AWG and two or three #14 to 10 AWG.  
Aluminum - #12 to #4 AWG and two or three #12 to #10 AWG.

If a hub is required, the catalog nos. below may be used.

Closure plate #11823  
3/4" J75  
1" J100  
1 1/4" J125

**Check all Pressure Wire  
Connectors, vibration in  
transit may loosen.**

ETL C.N 5023395  
104694718ACRT-002

General information: Circuit breaker trip position is indicated by handle position midway between on and off. To reset, move handle to the off position, then throw on. Circuit breakers are suitable for copper or aluminum conductors when marked.

Mount surface units at least 24 inches above ground level.

FOR INSTALLATION IN ACCORDANCE WITH ALL LOCAL  
ELECTRICAL AND / OR THE NATIONAL ELECTRICAL CODE (NEC)

